



#### Specifications

|               |                                                                                      |
|---------------|--------------------------------------------------------------------------------------|
| Size:         | 425/65R22.5                                                                          |
| Load / Speed: | 165K                                                                                 |
| Pattern:      | KMA400                                                                               |
| Brand:        | Leao                                                                                 |
| Category:     | TBR                                                                                  |
| Width:        | 425                                                                                  |
| Series:       | 65                                                                                   |
| Structure:    | R                                                                                    |
| Inch:         | 22.5                                                                                 |
| Ply Rating:   | 20PR                                                                                 |
| Load index:   | 165                                                                                  |
| Speed index:  | K                                                                                    |
| TL/TT:        | TL                                                                                   |
| Application:  | On/Off-road / sand                                                                   |
| Position:     |  |
| 40HC:         | 148                                                                                  |
| EAN Code:     | 8605068701764                                                                        |
| Factory code: | 211017086                                                                            |

#### Technical details

|                             |            |
|-----------------------------|------------|
| Recommended Rim:            | 13.00x22.5 |
| Inflation Pressure (bar):   | 8.25       |
| Section Width (mm):         | 430        |
| Outer Diameter (mm):        | 1124       |
| Static Load Radius (mm):    | 498        |
| Rolling Circumference (mm): | 3406       |
| Tread Depth (mm):           | 18.5       |
| Load (kg) @ Speed (km/h):   | 5150       |
| Weight (kg):                | 76.000     |

#### Label values

|                     |                |                                                                                       |
|---------------------|----------------|---------------------------------------------------------------------------------------|
| Rolling resistance: | D              |  |
| Wet / grip:         | B              |  |
| Sound:              | B (71 dB)      |  |
| Label code:         | <u>1327928</u> |                                                                                       |